

•

Lift Tables/ Lift Platforms

rev.20210914

Index

Introduction

| 1 |
|---|
| |

Lift Tables/Platforms

| Lift Table | |
|-----------------------------|---|
| Lift and Rotate Table 3 | |
| Lift and Tilt Table 4 | |
| Tilt Table 5 | |
| Slide - Tilt Table | |
| Cart Lift | |
| Cart Lift Table | |
| Other Lift Tables/Platforms | |
| Accessories | 0 |

Lift Table Air Bag Life Expectancy

The air bags used in Knight Global lift table products under normal conditions and cycle time have a life expectancy of approximately one million cycles or five years; whichever comes first. Knight strongly recommends that the air bags be replaced at these intervals. However, this may vary depending on plant conditions. Knight Global recommends complete quarterly maintenance inspections of the air bag actuated tables.

We are committed to **Total Customer Satisfaction** through QUALITY, RELIABILITY and EMPLOYEE INVOLVEMENT.

Knight Global | Warranty Information

Knight warrants that its products and parts shall meet all applicable specifications, performance requirements, and be free from defects in material and workmanship for one year, (Servo Systems for two years, Pneumatic Lift Tables for 5 years), from the date of invoice, unless otherwise noted. One exclusion would include any purchased components not manufactured by Knight and their specific individual warranties. Paint defects, scratches and marring from shipping are also excluded.

This warranty shall not cover the failure or defective operation caused by inadequate training provided by customer regarding the operation and / or maintenance of the tool, misuse, negligence, misadjustment, or any alteration not approved by Knight. Knight's obligation is limited to the replacement or repair of Knight's products at a location designated by Knight. Buyer is responsible for all associated internal removal and reinstallation costs as well as freight charges to and from Knight Industries. Knight's maximum liability shall not in any case exceed the contract price for the products claimed to be defective.

Any field modification made to Knight Products or Systems without the written authorization by Knight Global shall void Knight's warranty obligation.

Knight warrants the Servo Hoist, Arms, and Tractors to be free from defects in material or workmanship for a period of two years or 6000 hours use from the date of shipment.

Knight Distributors/ Agents are not authorized to circumvent or change any of these terms and or conditions of this warranty unless prior approval is received in writing by Knight Global Management. Verbal statements made by Knight Distributors/ Agents do not constitute warranties.

On a design and build job, the customer is the owner of the equipment once they authorize shipment. The purchased equipment can not be returned for reimbursement or credit.

DISCLAIMERS: OTHER THAN AS SET FORTH HEREIN, NO OTHER EXPRESSED WARRANTIES, AND NO IM-PLIED WARRANTIES, ORAL AND WRITTEN, INCLUD-ING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICU-LAR PURPOSE, ARE MADE BY KNIGHT GLOBAL WITH RESPECT TO ITS PRODUCTS AND ALL SUCH WAR-RANTIES ARE HEREBY SPECIFICALLY DISCLAIMED.

KNIGHTGLOBALSHALLNOTBELIABLEUNDERANYCIR-CUMSTANCESFORANYINCIDENTAL, SPECIALAND/OR CONSEQUENTIALDAMAGESWHATSOEVER, WHETH-ER OR NOTFORESEEABLE, INCLUDING BUT NOT LIM-ITED TO DAMAGESFOR LOST PROFITS AND ALL SUCH INCIDENTAL, SPECIALAND/OR CONSEQUENTIALDAM-AGESARE HEREBYALSOSPECIFICALLY DISCLAIMED.

KNIGHT GLOBAL WILL NOT BE LIABLE FOR ANY LOSS, INJURY OR DAMAGE TO PERSONS OR PROPERTY, NOR FOR DAMAGES OF ANY KIND RESULTING FROM FAILURE OR DEFECTIVE OPERATION OF ANY MA-TERIALS OR EQUIPMENT FURNISHED HEREUNDER.

Knight Lift Tables / Platforms

Knight Global Tables are ergonomically designed for easy loading and unloading of materials. Lift Tables are available in various styles, lift capacities and controls that will accommodate the needs of the application that your company is looking for. Lift tables incorporate the use of pneumatic control technologies, which makes the table operation cleaner, simplifies spare parts inventories and reduces general maintenance. Our exclusive Knight Global air bag design offers high durability and resistance to wear.





Maintenance Lock-Out Bars are standard on all tables. All tables are inspected and tested before they leave our facility.

Lift and Rotate Table

Features

- Lift, Lift and Rotate, Tilt, Lift and Tilt, Corner Tilt, Slide Tilt, Double Scissor Lift, Load Sensor, Zero Load Lift and Turntable Configurations Available.
- Steel Construction.
- Maintenance Lock-Out Bars.
- Heavy Duty Pneumatic Air Bags.
- Free-Standing Pedestal, Foot Control or Bolt on Hand Controls
- ContiTech FLEXAGrip[™] 400 P.S.I. rubber hose / fittings system.
- Maximum Capacity: Up to 6,000 lbs [2,721kg].

Options

- Steel Risers.
- Pit Mounted (Angled Toe Guards, External Mounted Pit Guards or Auto Safety Bars are required).
- Corner Gusset Tabs (No Extra Charge).
- Ratchet Safety Stops.
- Bellows Skirting.
- · Bolt-on Hand Control.
- Custom Control Packages
- Stainless Steel Hydraulic Hosing.

Note: Table and Lift Platforms are available with a variety of accessories, safety features and equipment. Optional Safety Equipment including but not limited to; perimeter fence guarding, bellows skirting, safety mats, audible signals, light signals, toe guards, special control guarding, etc. are not included unless otherwise stated in the product descriptions. Please check with your state, local or plant safety for requirements. Please contact your local Knight Global representative for more detailed information. Knight Global will be happy to quote any and all safety equipment needed to meet your requirements.


Knight Lift Table


Knight Lift Tables raise loads to the proper ergonomic heights for the operator for a safe and efficient workplace. Lift Tables reduce time lost to personnel injuries and helps increase productivity.

Polished chrome shafts are used at all slide and pivot points to minimize the wear and prolong component life. This lift table can be designed to fit a multitude of applications. Contact a Knight representative for more information



LIFT TABLE SPECIFICATIONS





| Model | Capacity Lbs [kg] | Closed (A) in [mm] | Extended (B) in [mm] | Base Size (Wb x Lb) in [mm] | Platform Size (Wp x Lp) in [mm] |
|---------------------|------------------------|----------------------------|----------------------------|---------------------------------------|--|
| L3636-2000 | 2000 [907] | | 24 [588] | 28 x 36 | 28 x 36 to 36 x 36 |
| L3636-4000 | 4000 [1814] | | 24[300] | [711 x 914] | [711 x 914] [914 x 914] |
| L4860-2000 | 2000[907] | 10 [254] | | 28 x 50 [711 x 1270] | 28 x 50 to 48 x 60 [711 x 1270] [1219 x 1524] |
| L4860-4000 | 4000 [1814] | | 37 [940] | 38 x 50 | 38 x 50 to 48 x 60 |
| L4860-6000 | 6000 [2722] | | | [965 x 1270] | [965 x 1270] [1219 x 1524] |
| L5684 - 4000 | 4000 [1814] | | | 42 x 62 | 42 x 62 to 56 x 84 |
| L5684-6000 | 6000 [2722] | 11 [279] | 45 [1143] | [1067 x 1575] | [1067 x 1575] [1422 x 2134] |

Note: Custom sizes are available on request. Please contact your Knight Global representative for more information.

Lift and Rotate Table




Knight Lift and Rotate Table

Knight Lift and Rotate Tables raise and rotate loads to the proper ergonomic heights for the operator and provide up to 360° of rotation. Lift and Rotate Tables reduce time lost to personnel injuries and helps increase productivity.


Knight Rotate Tables are available with our exclusive yoke supported bearings or a maintenance free 20,000 lbs. [9,072kg] capacity mechanical thrust bearing. Polished chrome shafts are used at all slide and pivot points to minimize wear and prolong component life.

LIFT AND ROTATE TABLE SPECIFICATIONS



| Model | Capacity Lbs [kg] | Closed (A) in [mm] | Rotation | Extended (B) in [mm] | Base Size (Wb x Lb) in [mm] | Platform Size (Wp x Lp) in [mm] | | |
|--------------|------------------------|----------------------------|----------|------------------------------|---------------------------------------|---|--------------------------|--------------------------------|
| LR4860C-2000 | 2,000 [907] | 12 [305] | | 26.5 [673] | 28 x 50 [711 x 1270] | 36 x 36 [914 x 914] to 48 x 60 | | |
| LR4860C-4000 | 4,000 [1,814] | | | [0/3] | [/11 x 12/0] | [1219 x 1524] | | |
| LR4860R-2000 | 2,000 [907] | 13 [330] | | | | | 28 x 36 [711 x 914] | 38 x 50 |
| LR4860R-4000 | 4,000 [1,814] | | | | | 360°)] | 40 [1,016] | to 28 x 50 [711 x 914] |
| LR4860R-6000 | 6,000 [2,722] | | | | to 38 x 50 [965 x 1270] | [1219 x 1524] | | |
| LR5684R-4000 | 4,000 [1,814] | 14 | | 48 | 42 x 62 | 42 x 62 [1067 x 1575] to | | |
| LR5684R-6000 | 6,000 [2,722] | [356] | | [1,219] | [1067 x 1575] | 56 x 84 [1422 x 2134] | | |

Note: Custom sizes are available on request. Please contact your Knight Global representative for more information.




Knight Tilt Table


Knight Tilt Tables tilt dunnage for easy loading or unloading, this feature makes for a safe and efficient workplace. Tilt Tables reduce time lost to personnel injuries and helps increase productivity.

Polished chrome shafts are used at all slide and pivot points to minimize the wear and prolong component life. Knight's Tilt Table can be designed to fit a multitude of applications. Contact a Knight representative for more information.



TILT TABLE SPECIFICATIONS





| Part Number | Capacity Lbs. [kg.] | Tilt | Closed (A) in. [mm.] | Base Size (Lb x Wb) in.[mm.] | Platform Size (Lp x Wp) in.[mm.] |
|----------------|--------------------------|--------|------------------------------|------------------------------------|--|
| T4860-2000 | 2,000 [907] | | | | |
| T4860-4000 | 4,000 [1,814] | 0°-40° | 8.5 [216] | Proportional to | 60 x 48 [1,524 x 1,219] to |
| T5684-2000 | 2,000 [907] | | [210] | Platform | 84 x 56 [2,134 x 1,422] |
| T5684-4000 | 4,000 [1,814] | | | | |

Note: Custom sizes are available on request. Please contact your Knight Global representative for more information.

Lift and Tilt Table





Knight Lift and Tilt Table

Knight Lift and Tilt Tables give the operator twice the ergonomic benefit by lifting and tilting loads to precise heights and angles, this also creates a safe and efficient workplace. Lift and Tilt Tables reduce time lost to personnel injuries and helps increase productivity.

Polished chrome shafts are used at all slide and pivot points to minimize wear and prolong component life. This lift table can be designed to fit a multitude of applications. Contact a Knight representative for more information.

LIFT AND TILT TABLE SPECIFICATIONS





| Model | Capacity Lbs [kg] | Closed (A) in[mm] | Extended (B) in [mm] | Tilt | Base Size (Lb x Wb) in [mm] | Platform Size (Lp x Wp) in[mm] | | | | | | |
|-------------|------------------------|-------------------------|------------------------------|--------|---------------------------------------|--------------------------------------|------------------------------------|--|--|--|----------------------------|----------------------------------|
| LT4860-2000 | 2,000 [907] | | | | | 38 x 50 | | | | | | |
| LT4860-4000 | 4,000 [1,814] | 16 [406] | 42 [1,066] | | | | | | | | 38 x 50 [965 x 1,270] | [965 x 1,270] to 60 x 48 |
| LT4860-6000 | 6,000 [2,722] | | | 0°-40° | | [1,524 x 1,219] | | | | | | |
| LT5684-4000 | 4,000 [1,814] | 17.25 | 17.25 | 50 | | 42 x 62 | 42 x 62 [1,066 x 1,575] to | | | | | |
| LT5684-6000 | 6,000 [2,722] | [438] | [1,270] | | [1,067 x 1,575] | 84 x 56 [2,134 x 1,422] | | | | | | |

Note: Custom sizes are available on request. Please contact your Knight Global representative for more information.

Slide - Tilt Table


Knight Slide - Tilt Table


Knight Slide - Tilt Tables maintain clearance on the unload side of the table with our patented slide and tilt motion, this also creates a safe and efficient workplace. Slide - Tilt Tables reduce time lost to personnel injuries and helps increase productivity.

Polished chrome shafts are used at all slide and pivot points to minimize wear and prolong component life. This lift table can be designed to fit a multitude of applications. Contact a Knight representative for more information.



SLIDE - TILT TABLE SPECIFICATIONS





| Part Number | Capacity Lbs. [kg.] | Tilt | Height (A) in. [mm.] | Platform Size (Wp x Lp) in. [mm.] | Base Size (Wb x Lb) in. [mm.] |
|----------------|--------------------------|-------|------------------------------|---|---------------------------------------|
| ST4860-2000 | 2,000 [907] | | | 36 x 55 | |
| ST4860-4000 | 4,000 [1,814] | | | [914 x 1,397] to 60 x 55 | |
| ST4860-6000 | 6,000 [1,814] | 10 | 0 10 | [1,524 x 1,397] | Proportional to |
| ST5684-2000 | 2,000 [907] | 0 -40 | [254] | 60 x 55 | Platform |
| ST5684-4000 | 4,000 [1,814] | | | [1,524 x 1,397] to 84 x 56 | |
| ST5684-6000 | 6,000 [1,814] | | | [2,134 x 1,422] | |



Knight Vertical Cart Lift - AIR

Knight's Cart Lift is an air cylinder actuated fork-free lift that raises carts to the operators working level for a safe and efficient workplace. They provide additional vertical travel distance in small footprint areas over typical scissor lifts.

Features and Options

- Floor Mounted or Portable units available.
- Ground Level Loading Height.
- Hand Control mounted on either side of the unit
- Right, Left or Center lift fork configurations available for the unit.
- Loads up to 1000 lbs

HD VERTICAL CART LIFT - Hydraulic

Knight's (Heavy Duty) HD Hydraulic Vertical Cart Lift is a fork-free lift that raises carts to the operators working level for a safe and efficient workplace. Cart Lifts provide additional vertical travel distance in small footprint areas over typical scissor lifts.

Features and Options

- Ground Level Loading Height.
- Front or Side Load Configurations.
- Floor Mounted or Portable units available.
- Pneumatic or Electric power controls for hydraulics.
- Hand Held Push Button.
- Pedestal or Foot Control.
- · Loads up to 3000 lbs



Knight Cart Lift Table


Knight's Cart Lift Tables are an air bag actuated fork-free lift that raises carts to the operators working level for a safe and efficient workplace. Cart Lift tables reduce time lost to personnel injuries and helps increase productivity. Knight's "Cart-to-Table" safety inter-lock system is standard on all cart lifts. This system disables the lift until the operator has positioned the cart in its correct location over the lift, triggering the circuit insuring the cart is engaged peoperly with the lift.


Features

- Max. Capacity: Up to 4,000 lbs. [1,814kg].
- Steel Construction.
- Maintenance Lock-Out Bars.
- Heavy Duty Pneumatic Air Bags.
- Cart Present Switches / Safety Interlock
- Polished Chrome Shafts at all Pivot and Slide Points.
- Steel Riser.
- Corner Gusset Tabs (No Extra Charge).
- Bellows Skirting.



CART LIFT TABLE SPECIFICATIONS





| Model | Capacity Lbs [kg] | Closed (A) in [mm] | Extended (B) in [mm] | Base Size (Wb x Lb) in [mm] | Platform Size (Wp x Lp) in [mm] |
|--------------|------------------------|------------------------------|--|---|---|
| CLS2650-2000 | 2000 [907] | 7[178] | 21.5 [546] to 26.5 [673] | 21 x 38 [533 x 965] to 21 x 50 [533 x 1270] | 28 x 36 [711 x 914] to 36 x 36 [914 x 914] |
| CLS2650-4000 | 4000 [1814] | | 21.5 [546] to 26.5 [673] | 21 x 38 [533 x 965] to 21 x 50 [533 x 1270] | 21 x 38 [533 x 965] to 26 x 50 [660 x 1270] |

Note: Table, Shuttles and Carts are available with a variety of accessories, safety features and equipment. Optional Safety Equipment including but not limited to; perimeter fence guarding, bellows skirting, safety mats, audible signals, light signals, toe guards, special control guarding, etc. are not included unless otherwise stated in the product descriptions. Please check with your state, local or plant safety for requirements. Please contact your local Knight Global representative for more detailed information. Knight Global will be happy to quote any and all safety equipment needed to meet your requirements.

Other Lift Tables / Platforms



Corner Tilt

Corner tilt table, tilts and positions a pallet or basket to the operators working level. Lifting capacity up to 4,000. [1,814kg].



Load Sensor Lift

Maintains loads at a safe ergonomic working height during varying weight load exchanges. Capacity up to 4,500 lbs. [2,041kg].



Air / Hydraulic / Electric Lift and Rotate Air or electric operated for the applications that need the rigid actuation that hydraulic provides.



Portable Lift Table Custom portable lift table is mounted to a cart for mobile use. Deck size and lift height will be customized to your application. Capacities vary by application.



Double Scissor Lift

When extra lift is needed to raise loads to a higher and safe ergonomic height. Capacity up to 2,000 lbs. [904kg].



Turntables

Supplies loads continuously to an assembly station with one, two or four position configurations. Capacity up to 6,000 lbs. [2,722kg].



Platform lifts the position of the operator in an ergonomic manner within a workstation. Pneumatic or hydraulic lifts available. Capacity up to 2,000 lbs. [904kg].




Zero Loader

Designed for ground level lifting and loading with a pallet jack when fork truck access is limited. Capacity up to 6,000 lbs. [2,722kg].



Zero Lift Loaders

Combines the convenience of ground level loading with the footprint of a standard lift table. Capacity up to 6,000 lbs .[2,722kg].



Smart Lift Table


Has the capability of interfacing with SGV's (self-guided vehicles) by intiating a "hand shake" signal when all positional conditions have been achieved. In the full down position, the sensors activate telling the SGV that it is clear to load or unload dunnage to the table. If any conditions are NOT met, the "hand shake" signal will not be made and the operation cannot continue.

Table Accessories



Hand and Foot Controls

Table controls are available in a pedestal mounted or floor mounted configuration.



Bellows Skirting

Protective covering that serves as a barrier for the operator. Skirting keeps debris from entering the table.



Motion Stabilizer

Stabiliizes loads traveling upward/downward in a smooth, consistent manner. Typically used for loads that are greater than 4,000 lbs. [1,814kg].



Steel Riser

The steel reinforced construction ensures a safe, sturdy mounting base. Standard and custom risers are available.